



Microline Dot Matrix Printers

ML720 ML721 9-Pin Dot Matrix Printer

High performance, versatile printer for dedicated forms printing

The ML720/ML721 narrow and wide carriage printers offer true flexibility making them ideal for practically any application. Engineered for productivity, the ML700 Series also has the levels of reliability synonymous with the Microline range. In short, versatility and robustness to meet your print requirements in the most demanding of work environments.

Highlights:

- OKI Printing Solutions reliability backed by 20,000H MTBF
- Optimised for high levels of throughput
- Integrated USB and IEEE Parallel Standard Interfaces
- Multi-copy capability (up to 6-part forms)
- Up to 570cps Super Speed Draft
- 128KB Buffer memory
- Low noise (56dB(A) in standard operation and 52dB(A) in quiet mode)



ML720/ML721

		ML720	ML721
General	Number of pins	9	
	No. of multi-part forms	6 (one original + 5 copies) (Carbon-lines paper & Pressure-sensitive-paper with Bottom feed)	
Speed and throughput	Super speed (12cpi)	570cps	
	High speed draft (10cpi)	507cps	
	Utility	380cps	
	Near letter quality	95cps	
	Fastest print speed	570cps	
Font & print features	Carriage width (10cpi)	80 Columns	136 Columns
	Max. in compression mode	160 Columns	272 Columns
	Character pitch	10/12/15/17.1/20 pitch & proportional	
	Graphics resolution	Up to 240 x 216 dpi	
	Typeface & Font	NLQ-Courier (Scalable), NLQ-Gothic (Scalable), OCR-B, High Speed Draft, Utility + Barcodes	
Emulations & Interfaces	Printer emulations	Epson FX, IBM ProPrinter, Oki Microline	
	Standard interfaces	Centronics Parallel + USB	
	Optional interfaces	Serial RS 232C / Ethernet	
Paper handling	Continuous paper	76.2 - 254mm	76.2 - 406.4mm
	Continuous envelopes	Width 76.2 - 254mm (Bottom feed only)	
	First printable line (from top of page)	Cut-sheet: 0.5mm, Continuous: 0.5mm	
	Standard	Paper parking, Low tear-off, Push tractors, Autoload single sheet	
	Optional	Pull tractor, Single/dual bin sheet feeder, Roll paper stand (80 column only), Bottom push tractor	
Physical	Dimensions (HxWxD)	153 x 398 x 345mm <small>(Without Platen knob, Acoustic cover and Paper separator)</small>	153 x 552 x 345mm <small>(Without Platen knob, Acoustic cover and Paper separator)</small>
	Weight	7.5kg	9.5kg
	Memory	128KB	
	Noise level	56dB(A) normal operation / 52dB(A) in quiet mode	
Power	Power requirements	230V AC	
	Frequency	50/60Hz	
Reliability	Print head life	200 million characters	
	Ribbon life	4 million characters (re-inking cartridge)	
	MTBF	20,000 hours	

Consumables Information: Only use genuine OKI Printing Solutions Original consumables to ensure the best quality and performance from your hardware. Non OKI Printing Solutions Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

OKI DATA AUSTRALIA PTY. LTD.

Level 1, 67 Epping Road
Macquarie Park, NSW 2113
Australia
T 1800 800 140
www.oki.com/au

OKI DATA NEW ZEALAND

F2 3 Orbit Drive, Rosedale
Auckland 0632
New Zealand
T 0800 654 669
www.oki.com/nz

OKI

Open up your dreams