#### C SERIES MONITORS

### **DELL 24/27 VIDEO CONFERENCING MONITORS - C2423H, C2723H**

#### Facial authentication

Sign-in to your Windows 10 devices, apps and websites with the facial recognition feature. Biometric sensors activate and scan your face, eliminating the threat of hacking and providing enterprise-level security.

video conference

#### Collaborate like you are there

Launch the pop-up FHD webcam to engage into meeting quickly and easily. Pop-down the webcam to switch to voice-only mode for added privacy.

#### Manage multiple tasks

. . .

Enhance efficiency by 21%\*\* by adding a second monitor via Dell Express Daisy Chaining through DisplayPort connectivity.

#### Extensive connectivity

Easily connect to a variety of devices with extensive connectivity ports, including DisplayPort, HDMI and 4x SuperSpeed USB 5Gbps.

Built-in ComfortView Plus reduces harmful blue light emissions without sacrificing color performance.

#### Great views from all angles Full HD video and screen

resolution with 30 fps rate delivers seamless video and screen clarity. IPS panel with 178°/178° wide viewing angle presents superior views and consistent colors ideal for video conferencing.

. . .

Adjust to your comfort Tilt, swivel, and height adjustable (150mm max).

#### Easy-access mute button o

Quick access to the mute button at the front of the display

Listen and be heard: An echo and noise-cancelling mic with two 5W integrated speakers deliver clear audio, so you never miss out during a meeting.

Functional design

Features 3-sided ultrathin bezel design, a small base and improved cable management for a clutter free desk at your home or at your office.

### THE WORLD'S # 1 MONITOR COMPANY\*



\* Dell monitors are #1 Worldwide for 8 consecutive years (2013, Q2 to 2021, Q2)! Source: IDC Worldwide Quarterly PC Monitor Tracker, Q2, 2021.

\*\* Source: Based on Principled Technologies Report commissioned by Dell, November 2018. Actual results will vary. Full report: https://www.principledtechnologies.com/Dell/P2419H\_ monitor\_productivity\_1118.pdf





### c series monitors C2423H, C2723H



#### STEADFAST RELIABILITY

#### Peace of mind

Dell Premium Panel Exchange<sup>1</sup> allows a free monitor replacement during the Limited Hardware Warranty<sup>2</sup> period, even if only one bright pixel is found.

#### Minimize downtime

Your monitor comes with a 3-year Advanced Exchange Service<sup>3</sup> so that if a replacement becomes necessary, it will be shipped to you the next business day during your 3-year Limited Hardware Warranty.<sup>2</sup>

#### Get a higher level of support

Upgrade to 24x7 specialized technical phone support with the Dell ProSupport option.<sup>4</sup>

#### RECOMMENDED ACCESSORIES



#### Dell Pro Wireless Headset | WL5022

Enjoy wireless freedom away from your PC with this Teams certified headset that offers convenient call controls. Switch seamlessly across your PC, tablet or smartphone and enjoy superior audio clarity on the go.



#### Dell Pro Wireless Keyboard and Mouse | KM5221W

Elevate productivity with this wireless full size narrow bezel keyboard and ambidextrous mouse combo with 3 years of battery life<sup>5</sup>.



#### Dell Dual Monitor Arm | MDA20

Quickly install this Dell Dual Monitor Arm – MDA20 for a comprehensive monitor and system mounting solution. This virtually tool-free installation makes deployment simple.

#### PORTS AND SLOTS



- Power connector
   Security lock slot (based on Kensington Security Slot<sup>™</sup>)
   HDMI port
- 4 Stand lock feature
  5 DisplayPort
  6 DisplayPort (out)
- 7 SuperSpeed 5Gbps USB 5Gbps (USB 3.2 Gen1) Type-B upstream port
  8 SuperSpeed 5Gbps USB 5Gbps (USB 3.2 Gen1) Type-A downstream port
- 9 SuperSpeed 5Gbps USB 5Gbps (USB 3.2 Gen1) Type-A downstream port with Power Charging (BC 1.2)
   10 Headphone Jack
- 11 Built-in speakers

- 1 Applicable to Dell UltraSharp, P Series, and C Series desktop monitors.
- 2 For copy of Ltd Hardware Warranty, write to Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see https://www.dell.com/warranty.
- 3 Advanced Exchange: Dell will send you a replacement monitor the next business day in most cases if deemed necessary after phone/online diagnosis. Shipping times may vary by location and for monitors 55" and above. Fee charged for failure to return defective unit. See dell.com/servicecontracts/global.
- 4 Availability varies, please visit www.dell.com/support for details. In some countries, hours for in-region support may vary. Support after local business hours may be provided in a language other than the local language.
- 5 Based on Dell internal analysis of battery life usage model calculations and 3 million keystrokes per year, Nov 2019. Results vary depending on usage and computing conditions.

# C SERIES MONITOR

# C SERIES MONITOR

MONITOR		MONITOR	
NAME	Dell 24 Video Conferencing Monitor - C2423H	NAME	Dell 27 Video Conferencing Monitor - C2723H
DIAGONAL VIEWING SIZE	604.70 mm (23.80 in.)	DIAGONAL VIEWING SIZE	685.80 mm (27.00 in.)
HORIZONTAL	527.04 mm (20.75 in.)	HORIZONTAL	597.89 mm (23.54 in.)
VERTICAL	296.46 mm (11.67 in.)	VERTICAL	336.31 mm (13.24 in.)
MAXIMUM PRESET RESOLUTION	1920 x 1080 at 60 Hz	MAXIMUM PRESET RESOLUTION	1920 x 1080 at 60 Hz
ASPECT RATIO	16:9	ASPECT RATIO	16:9
PIXEL PITCH	0.2745 mm x 0.2745 mm	PIXEL PITCH	0.3114 mm x 0.3114 mm
PIXEL PER INCH (PPI)	92.53	PIXEL PER INCH (PPI)	81.59
BRIGHTNESS	250 cd/m² (typical)	BRIGHTNESS	300 cd/m² (typical)
COLOR SUPPORT	sRGB 99% (typical)	COLOR SUPPORT	sRGB 99% (typical)
	Color depth: 16.78 Million		Color depth: 16.78 Million
CONTRAST RATIO	1000:1 (typical)	CONTRAST RATIO	1000:1 (typical)
VIEWING ANGLE	178°/178°	VIEWING ANGLE	178°/178°
RESPONSE TIME	5 ms (Fast mode) 8 ms (Normal mode)	RESPONSE TIME	5 ms (Fast mode) 8 ms (Normal mode)
PANEL TYPE	In-Plane Switching Technology	PANEL TYPE	In-Plane Switching Technology
DISPLAY SCREEN COATING	Anti-Glare	DISPLAY SCREEN COATING	Anti-Glare
BACKLIGHT TECHNOLOGY	LED	BACKLIGHT TECHNOLOGY	LED
COMFORTVIEW PLUS WITH FLICKER-FREE SCREEN	Yes	COMFORTVIEW PLUS WITH FLICKER-FREE SCREEN	Yes
DELL DISPLAY MANAGER COMPATIBILITY	Yes	DELL DISPLAY MANAGER COMPATIBILITY	Yes
REMOTE ASSET MANAGEMENT	Yes, via Dell Command I Monitor	REMOTE ASSET MANAGEMENT	Yes, via Dell Command I Monitor
GSA/TAA	No	GSA/TAA	No
OPTIONAL SOUNDBAR	No	OPTIONAL SOUNDBAR	No
CONNECTIVITY		CONNECTIVITY	
CONNECTORS	<ul> <li>1 x DisplayPort version 1.2 (HDCP 1.4)</li> <li>1 x HDMI port version 1.4 (HDCP 1.4)</li> <li>1 x DisplayPort (Out) with MST</li> <li>1 x USB Type-B (USB3.2 Gen1) upstream port</li> <li>2 x SuperSpeed USB 5Gbps (USB 3.2 Gen1) downstream port</li> <li>2 x SuperSpeed USB 5Gbps (USB 3.2 Gen1) downstream port with BC1.2 charging capability at 2A (maximum)</li> <li>1 x 3.5mm headphone jack</li> </ul>	CONNECTORS	<ul> <li>1 x DisplayPort version 1.2 (HDCP 1.4)</li> <li>1 x HDMI port version 1.4 (HDCP 1.4)</li> <li>1 x DisplayPort (Out) with MST</li> <li>1 x USB Type-B (USB3.2 Gen1) upstream port</li> <li>2 x SuperSpeed USB 5Gbps (USB 3.2 Gen1) downstream port</li> <li>2 x SuperSpeed USB 5Gbps (USB 3.2 Gen1) downstream port with BC1.2 charging capability at 2A (maximum)</li> <li>1 x 3.5mm headphone jack</li> </ul>
HDCP SUPPORT	HDMI HDCP 1.4 DP HDCP 1.4	HDCP SUPPORT	HDMI HDCP 1.4 DP HDCP 1.4
WEBCAM AND MICROPHONE		WEBCAM AND MICROPHONE	
LENS		LENS	
FIELD OF VIEW	88.9 degrees for 2560 x 1920	FIELD OF VIEW	88.9 degrees for 2560 x 1920
FOCUS MODE	Fixed focus	FOCUS MODE	Fixed focus
FOCUS AREA	35 cm ~ 1.5 m	FOCUS AREA	35 cm ~ 1.5 m
FOCUSING DISTANCE (NORMAL MODE)	70 cm	FOCUSING DISTANCE (NORMAL MODE)	70 cm
IMAGE SENSOR ACTIVE ARRAY SIZE	5 mega-pixel	IMAGE SENSOR ACTIVE ARRAY SIZE	5 mega-pixel
VIDEO FRAME RATE	1920x1080 (Full HD) - up to 30 frames per second	VIDEO FRAME RATE	1920x1080 (Full HD) - up to 30 frames per second
MICROPHONE TYPE	Digital microphone x 2	MICROPHONE TYPE	Digital microphone x 2
INTERFACE	USB 2.0 high speed	INTERFACE	USB 2.0 high speed
POWER SUPPLY	3.3 volts +/- 5% for USB and Microphone 5 volts +/- for IR camera	POWER SUPPLY	3.3 volts +/- 5% for USB and Microphone 5 volts +/- for IR cameras

## C SERIES MONITOR

## C SERIES MONITOR

02720			••
SPEAKER		SPEAKER	
SPEAKER RATED POWER	2 x 5 W	SPEAKER RATED POWER	2 x 5 W
FREQUENCY RESPONSE	200 Hz - 16 kHz	FREQUENCY RESPONSE	200 Hz - 16 kHz
IMPEDENCE	8 ohm	IMPEDENCE	8 ohm
DESIGN FEATURES		DESIGN FEATURES	
ADJUSTABILITY	Height adjustability stand 150mm Tilt -5° to 21° Swivel -45° to 45° Pivot -90° to 90°	ADJUSTABILITY	Height adjustability stand 150mm Tilt -5° to 21° Swivel -45° to 45° Pivot -90° to 90°
SECURITY	Security lock slot (cable lock sold separately)	SECURITY	Security lock slot (cable lock sold separately)
FLAT PANEL MOUNT INTERFACE	VESA (100 mm)	FLAT PANEL MOUNT INTERFACE	VESA (100 mm)
POWER		POWER	
AC INPUT VOLTAGE/FREQUENCY/ CURRENT	100 VAC to 240 VAC / 50 Hz or 60 Hz $\pm$ 3 Hz / 1.5 A (typical)	AC INPUT VOLTAGE/FREQUENCY/ CURRENT	100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 1.5 A (typical)
POWER CONSUMPTION (OPERATIONAL)	0.3 W (Off mode) 0.3 W (Standby Mode) 12.6 W (On mode) 82 W (Max.)	POWER CONSUMPTION (OPERATIONAL)	0.2 W (Off mode) 0.3 W (Standby Mode) 13.2 W (On mode) 85 W (Max.)
POWER CONSUMPTION STAND BY/SLEEP	Less than 0.3W	POWER CONSUMPTION STAND BY/SLEEP	Less than 0.3W
DIMENSIONS (WITH STAND)		DIMENSIONS (WITH STAND)	
HEIGHT	496.10 mm (19.53 in.)	HEIGHT	534.15 mm (21.03 in.)
WIDTH	537.80 mm (21.17 in.)	WIDTH	609.90 mm (24.01 in.)
DEPTH	179.57 mm (7.07 in.)	DEPTH	190.10 mm (7.48 in.)
WEIGHT		WEIGHT	
WEIGHT (PANEL ONLY - FOR VESA MOUNT/ NO CABLES)	3.83 kg (8.44 lb)	WEIGHT (PANEL ONLY - FOR VESA MOUNT/ NO CABLES)	5.04 kg (11.11 lb)
WEIGHT (MONITOR AND CABLES WITH STAND)	6.02 kg (13.27 lb)	WEIGHT (MONITOR AND CABLES WITH STAND)	7.24 kg (15.96 lb)
WEIGHT (WITH PACKAGING)	8.33 kg (18.36 lb)	WEIGHT (WITH PACKAGING)	10.01 kg (22.07 lb)
STANDARD SERVICE PLAN	3 Years Advanced Exchange Service, Premium Panel Guarantee and Limited Hardware Warranty	STANDARD SERVICE PLAN	3 Years Advanced Exchange Service, Premium Panel Guarantee and Limited Hardware Warranty
OPTIONAL SERVICE PLAN	Dell ProSupport	OPTIONAL SERVICE PLAN	Dell ProSupport
ENVIRONMENTAL COMPLIANCE	<ul> <li>ENERGY STAR certified monitor</li> <li>EPEAT registered where applicable. EPEAT registration varies by country. See www. epeat.net for registration status by country.</li> <li>RoHS-compliant</li> <li>TCO Certified and TCO Certified Edge</li> <li>BFR/PVC free monitor (excluding external cables)</li> <li>Meets NFPA 99 leakage current requirements</li> <li>Arsenic-free glass and Mercury-free for the panel only</li> </ul>	ENVIRONMENTAL COMPLIANCE	<ul> <li>ENERGY STAR certified monitor</li> <li>EPEAT registered where applicable. EPEAT registration varies by country. See www. epeat.net for registration status by country.</li> <li>RoHS-compliant</li> <li>TCO Certified and TCO Certified Edge</li> <li>BFR/PVC free monitor (excluding external cables)</li> <li>Meets NFPA 99 leakage current requirements</li> <li>Arsenic-free glass and Mercury-free for the panel only</li> </ul>
WHAT'S IN THE BOX		WHAT'S IN THE BOX	
COMPONENTS	Monitor with stand	COMPONENTS	Monitor with stand
CABLES	Power cable	CABLES	Power cable
	1 x DisplayPort to DisplayPort cable (1.8 meters)		1 x DisplayPort to DisplayPort cable (1.8 meters)
	1 x HDMI cable (1.8 meters)		1 x HDMI cable (1.8 meters)
	1 x USB Type A to USB Type B cable (1.8 meters)		1 x USB Type A to USB Type B cable (1.8 meters)
DOCUMENTATION	Quick Setup Guide	DOCUMENTATION	Quick Setup Guide
	Safety and regulatory information		Safety and regulatory information

### **D&LL**Technologies

Technical specifications subject to change without prior notice. Product availability varies by country. Please contact your Dell representative for more information.

© 2022 Dell Inc. or its subsidiaries. All rights reserved. Dell Technologies, Dell, EMC, Dell EMC and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners. USB Type-C<sup>®</sup> and USB-C<sup>®</sup> are registered trademarks of USB Implementers Forum.